

SINGLE-LEAF

Single-leaf doors

Opening from 700 to 1500 mm.

AVAILABLE FOR:

Series Basic
Code: ABS040

Series Strong
Code: ABS060

Series Green Fast
Code: ABS0GF

Series Mdf
Code: ABS0MD

Wide range of options available
on request (see pag. 27)



DOPP DOUBLE-LEAF IO BATTENTE

Double-leaf doors

Opening from 1400 to 3000 mm.

AVAILABLE FOR:

Series Basic
Code: ABD040

Series Strong
Code: ABD060

Series Green Fast
Code: ABD0GF

Series Mdf
Code: ABD0MD

Wide range of options available
on request (see pag. 27)



DOUBLE OPPOSING SLIDING DOORS

Double opposing sliding doors with upper guide

Opening from 700 to 3000 mm.

AVAILABLE FOR:

Series Basic
Code: ASS040 AL

Series Strong
Code: ASS060 AL

Series Green Fast
Code: ASS0GF AL

Series Mdf
Code: ASS0MD AL

Wide range of options available
on request (see pag. 27)



SLIDING DOORS WITH UPPER GUIDE

Single sliding doors
Opening from 700 to 3000 mm.

AVAILABLE FOR:

Series Basic

Code: ASS040

Series Strong

Code: ASS060

Series Green Fast

Code: ASS0GF

Series Mdf

Code: ASS0MD

Wide range of options available
on request (see pag. 27)



SLIDING DOORS WITHOUT GUIDE

Sliding doors without guide
Opening from 1500 to 6000 mm.

Wide range of options available
on request (see pag. 27)

Compatible with all SATECH
assembly systems

Motorization available on request

AVAILABLE FOR:

Series Strong

Code: ASG060



SLIDING DOORS WITH LOWER GUIDE

Sliding doors with lower guide
Opening from 700 to 3000 mm.

AVAILABLE FOR:

Series Basic

Code: AST040

Series Strong

Code: AST060

Series Green Fast

Code: AST0GF

Series Mdf

Code: AST0MD

Wide range of options available
on request (see pag. 27)



OPPOSING SLIDING DOORS WITH UPPER GUIDE

Opposing sliding doors with upper guide
Opening from 1400 to 3000 mm.

AVAILABLE FOR:

Series Basic

Code: ASSC040

Series Strong

Code: ASSC060

Series Green Fast

Code: ASSCOGF

Series Mdf

Code: ASSCOMD

Wide range of options available
on request (see pag. 27)



SINGLE SLIDING DOORS WITH TELESCOPIC GUIDE

Single sliding doors with Satech's telescopic guide
Opening from 700 to 1500 mm.

AVAILABLE FOR:

Series Basic

Code: ASTE040

Series Strong

Code: ASTE060

Series Green Fast

Code: ASTE0GF

Wide range of options available
on request (see pag. 27)



OPPOSING SLIDING DOORS WITH TELESCOPIC GUIDE

Opposing sliding doors with telescopic guide
Opening from 1400 to 3000 mm.

AVAILABLE FOR:

Series Basic

Code: ASTEC040

Series Strong

Code: ASTEC060

Series Green Fast

Code: ASTEC0GF

Wide range of options available
on request (see pag. 27)



FOLDING DOORS

Folding Doors.

Opening from 1400 to 3000 mm.

AVAILABLE FOR:

Series Basic

Code: ABL040

Series Strong

Code: ABL040

Series Green Fast

Code: ABL040

Series Mdf

Code: ABL040

Wide range of options available
on request (see pag. 27)



SPECIAL AUTOMATIC

The proposed standard solutions are provided with electromechanical motorization with mechanical or electronic adjustment of movement parameters. If required by the customer, pneumatic moving systems, including vertical ones, can be easily applied.

Compatible with all SATECH
assembling systems



SPECIAL TELESCOPIC

Satech designs and produces special doors with multiple functions. The available combinations are:

- > With panels sliding on linear guides.
- > With folding panels.
- > With leaf elements in sliding doors with linear guides.
- > With double combined movement of sliding and leaf doors

Compatible with systems
Basic, Strong and Green Fast



SPECIAL VERTICAL

The use of robotized cells in industrial automation requires to limit the perimeter of protections and to move door panels in vertical direction. The original design of Satech's doors with vertical sliding optimizes the use of space and assures the maximum safety and perfect functionality of the system.

Compatible with all SATECH assembling systems



SPECIAL LARGE ACCESSES

Satech's technical department has acquired considerable experience in the development of special solutions allowing large openings, obtained by easy operation and extremely strong components. Satech have produced combined sliding-hinged doors with opening **over 10 meters**.

Compatible with all SATECH assembling systems



OPTIONAL:



- Ergonomic handle
- Pairs of hinges or pivot pins
- Upper crosspiece
- Upper crosspiece with ledge
- Magnetic locking system
- Ground supporting wheel
- Ground stop
- Panic lock
- Key lock
- 3rd level lock
- 4th level lock
- Bolt with padlock
- Universal brackets for safety microswitches
- Hinged safety microswitch
- Clutch Safety microswitch
- Galvanized steel upper guide
- Steel trolleys with threaded connection
- Lower Slideways
- Upper slideways
- Galvanized lower guide
- Steel wheels with V groove
- Satech telescopic guide
- Tyred wheel
- Electric motorization